

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	x
	LIST OF FIGURES	xii
	LIST OF SYMBOLS	xiii
	LIST OF APPENDICES	xvi
1	INTRODUCTION	1
	1.1 Introduction	1
	1.2 Background of the Study	3
	1.3 Problem Statement	3
	1.4 Aims and Objectives	4
	1.5 Scope of the Study	4
	1.6 Research Methodology	5
	1.7 Significance of the Study	7
	1.8 Organization of the Study	7

2	LITERATURE REVIEW	8
2.1	Optical Soliton	8
2.2	Coupled-Mode Theory for FBG	9
2.3	Soliton in Fiber Bragg Grating	12
2.4	Pulse propagation in FBG	13
2.5	Properties of Fiber Bragg Grating	15
2.5.1	Bragg condition	15
2.5.2	Uniform Bragg grating reflectivity	17
2.6	Photosensitivity in Optical Fiber	19
2.7	Fabrication Technique for Fiber Bragg Grating	21
2.7.1	Internal Inscription of Bragg Gratings	21
2.7.2	External Inscription of Bragg Gratings	23
2.7.3	Point-by-point Writing Technique	25
2.7.4	The Phase Mask Technique	26
3	EXPERIMENTAL SETUP	28
3.1	Introduction	28
3.2	Experimental Setup of Fiber Bragg Grating	
	Fabrication	28
3.2.1	KrF Excimer Laser Overview	31
3.2.2	Mask Aligner Overview	34
3.2.3	Phase mask	36
3.2.4	Tunable Laser Source	36
3.2.5	Optical Spectrum Analyzer	37
4	FIBER BRAGG GRATING MODEL OF POTENTIAL ENERGY DISTRIBUTION	39
4.1	Coupled Mode Theory	39
4.2	Derivation of Nonlinear Coupled Mode Equation (NLCM)	43
4.3	Derivation of Potential Energy Distribution in Fiber Bragg Grating	49
4.4	Modelling of Optical Soliton using NLCM	50

4.5	Modelling of Potential Energy Distribution in Fiber Bragg Grating structures	53
4.6	Multi Perturbation of Potential Energy Photon in Fiber Bragg Grating	53
4.6.1	External Perturbation of Potential Energy	53
4.7	Flowchart for computational modelling	55
5	RESULTS AND DISCUSSION	59
5.1	Introduction	59
5.2	Results of Fiber Bragg Grating Fabrication	59
5.3	Results for Simulation of Soliton in Fiber Bragg Grating	62
5.3.1	Nonlinear Parametric Studies of Photon in Fiber Bragg Grating	62
5.3.2	External Disturbance of Potential Energy Photon in Fiber Bragg Grating	65
5.3.3	Motion of Photon due to External Energy Perturbation in Potential Well	68
5.4	Summary	72
6	CONCLUSION	73
6.1	Introduction	73
6.2	Conclusions	73
6.3	Future Work	75
7	REFERENCES	76
8	APPENDICES	79
9	PUBLISHED PAPERS	93

LIST OF TABLES

TABLE NO.	TITLE	PAGE
5.1	Summary of the data collected for fabrication	62

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
1.1	Illustration of Fiber Bragg Grating.	1
1.2	The flow chart for the research methodology on the novel idea of using optical soliton in FBG.	6
2.1	Cross-section of an optical fiber with the corresponding refractive index profile.	11
2.2	A basic diagram of Fiber Bragg Grating	16
2.3	Oxygen-deficient germania defects thought to be responsible for the photosensitive effect in germania-doped silica.	20
2.4	Schematic of original apparatus used for recording Bragg Gratings in optical fibers. A position sensor monitored the Amount of stretching of the Bragg gratings as it was strain-tuned to measure its very narrow-band response.	22
2.5	Schematic design of the diffraction of an incident beam from a phase mask.	27
3.1	Schematic diagram of Fiber Bragg Grating fabrication experimental setup.	29
3.2	KrF Excimer Laser	33
3.3	Functional design of the COMPeX laser system	33
3.4	Optical components of mask aligner	35
3.5	Schematic diagram on propagation of light in mask aligner	35
3.6	Phase Mask Holder	36
3.7	Tunable Laser Source Overview	37

3.8	The Optical Spectrum Analyzer	38
4.1	Flow chart in the case where there is no energy disturbance	55
4.2	Flow chart of simulation with potential energy disturbance factor	56
4.3	Flow chart of potential energy under multi-perturbation condition	57
5.1	The transmission spectrum to monitor the growth of fiber grating in FBG1	60
5.2	Results of fabricated FBG1	61
5.3	The motion of photon in double well for different values of α	63
5.4	The optimized point of the double well potential for different values of α	63
5.5	Under Bragg resonance condition the system possesses double well potential for $\gamma = 0.13$ to 0.53	64
5.6	The optimized point of the double well potential when $\gamma = 0.1$ to 1.0	65
5.7	The motion of photon in potential well for $\alpha = 0.9$, $\beta = 0.3$, $\theta = 0.09$ and γ is varies from 0.3 to 0.9 .	66
5.8	The effect of theta, θ to γ and shape of the potential well of the photon.	67
5.9	The disturbance to the potential energy by β factor	68
5.10	The motion of photon in potential well for $\alpha = 0.9$, $\beta = 0.3$, $\theta = 0.09$ and γ is varies from 0.3 to 0.9 .	69
5.11	The disturbance factor that affect the shape of the potential well of the motion of photon.	71

LIST OF SYMBOLS

λ_B	-	Bragg wavelength
Λ	-	Spatial period (or pitch) of the periodic variation
N_{eff}	-	Effective index for light propagating in a single mode fiber
$A(z)$	-	Forward propagating modes
$B(z)$	-	Backward propagating modes
$\psi(x, y)$	-	Transverse modal field distribution
ω	-	Frequency
β	-	Propagation constant of the mode
$n_g^2(x, y, z)$	-	Refractive index variation along the fiber
K	-	Spatial frequency of the grating
Δn^2	-	Index modulation of the grating
Γ	-	Coupling coefficient
r	-	Radius of the core of FBG
a	-	Radius of the cladding of FBG
l	-	Length of the grating
R	-	Reflectivity of the grating
n_2	-	Kerr coefficient
$\delta n_g(z)$	-	Periodic index variation inside the grating
$n_2 I$	-	Nonlinear index change
\bar{n}	-	Average refractive index of the medium
$\varepsilon(z)$	-	Perturbed permittivity
$E_{f,b}(z, t)$	-	Forward and backward propagating waves

κ	-	Coupling between the forward and backward propagating waves in the FBG
k_i	-	Incident wavevector
K	-	Grating wavevector
k_f	-	Wavevector of the scattered radiation
n_{eff}	-	Effective refractive index of the fiber core at free space center wavelength
Δn	-	Amplitude of the induced refractive index perturbation formed in the core of the fiber
z	-	Distance along the fiber in longitudinal axis
$R(l, \lambda)$	-	Reflectivity
λ	-	Wavelength
Ω	-	Coupling coefficient
Δk	-	Detuning wavevector
K	-	Propagation constant
M_p	-	Fraction of the fiber mode power contained by the fiber core
V	-	Normalized frequency of the fiber
n_{co}	-	Core radius
n_{cl}	-	Cladding radius
λ_w	-	Irradiation wavelength
φ	-	Intersecting beams
Λ_g	-	Period of the grating
Λ_{pm}	-	Period of the phase mask
Λ_g	-	Period of fringes
λ_{uv}	-	UV wavelength
N	-	Number of grating
$\bar{P}_{unperturbed}$	-	Unperturbed polarization
$\bar{P}_{grating}$	-	Perturbed polarization
μ	-	Transverse mode number
\hat{e}_z	-	Unit vector along the propagation direction z
$\delta_{\mu\nu}$	-	Kronecker's delta

\vec{E}	-	Electric field vectors
\vec{H}	-	Magnetic field vectors
\vec{D}	-	Displacement vectors
\vec{B}	-	Flux density
c	-	Speed of light
$\vec{E}(z, t)$	-	Electric field
ω_0	-	Central frequency
k_0	-	Wavenumber
P_0	-	Total power inside the grating
e_f	-	Forward propagating modes
e_b	-	Backward propagating modes
Γ_s	-	Self Phase Modulation
Γ_x	-	Cross-phase modulation effects
C	-	Constant of integration
$\hat{\delta}$	-	Detuning parameter
$V(A_0)$	-	Potential energy distribution in a FBG structures while the light propagating through the grating structures

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	The transmission spectrum to monitor the growth of fiber grating during FBG fabrication using phase mask technique	79
B	Characteristics of fabricated FBGs based on the transmission spectrum	81
C	MatLab coding of potential energy distribution in Bragg grating	83
D	MatLab coding for optimizing photon trapping under the effects of nonlinear parameters, α , β , γ and θ in an FBG	85
E	Matlab coding of potential well insertion of θ factor when soliton propagates in FBG	87
F	MatLab coding for higher order disturbance factor under multi-perturbation factor	89